



Cardas Audio

Clear High Speed Serial Buss (USB)

Performance

Clear High Speed Serial Buss takes our Clear Serial Buss USB cable and adds a special high performance data cable using silver-plated conductors. Each conductor pair in both cables is discreetly shielded, and each cable has its own double-shield.

This ultra-premium USB cable adds depth & realism, and improved imaging to your digital system. A noticeable improvement over our already high performing Clear Serial Buss.

Clear High Speed Serial Buss USB is ideal for use with high resolution digital audio.

Standard Terminations: USB A to B

Design/Construction

Conductors: Matched Propagation Kevlar core, ultra fine Grade 1, 99.9999% pure

oxygen free copper with SPN clear coat (Litz), gauge sizes scaled to Golden Ratio proportions. Cross-field layer geometry, insulated in ultra thin extruded PTFE jacket. Solid core copper silver plated data conductors.

Geometry: Dual asymmetrical star-quad 8 conductor. Signal carrying conductors are a shielded twisted pair. Power and signal conductors are bound with PFA tape. Final shield is aluminum/mylar, tin plated copper and magnet wire. Outer jacket is TPR.

Gauge: 2x25.5 AWG + 2x21.5 AWG + 23.5 AWG + 30 AWG

Outside Diameter: Approximately 0.453"/11.50mm